

The H-Series Manway™

The KING of Pharmaceutical Manways.

The H-Series Manway has an impressive 25 year history. With 10,000+ manways in service today, the H-Series is the STANDARD.



Product Features

- Sanitary, pharmaceutical design
- Handles higher pressures with fewer lugs, providing easier access
- Standardized clamp / lug assemblies
- 1/4" Plate cover & collar on sizes 8" - 26" manways
- 5/16" Plate cover & 1/4" plate collar on sizes 28" - 48" manways
- 6" standard collar length (Collars up to 72" are available)
- Provided with a standard hinge heavy duty hinge & handle
- Optional stainless enclosed spring assist is available
- O-Ring groove is available in the cover or collar ring
- Standard O-Rings are 5/16" Cross Section



* 18" (5) Lug H-Series is shown

Materials & Finishes

- T-316L (Standard), T-304L, C-22, C-276, AL6XN, others available
- All interior welds are ground "Smooth & Flush"
- All Exterior welds can be ground "Smooth & Flush", "Buffed", or left "As-Is"
- Finishes are available from a Mill (HRAP) finish to a 10 Ra (320 Grit)

Standard O-Ring Gasket Materials

- | | |
|-------------------------------|--|
| • Red Silicone (FDA) | • Black EPDM (USP Class VI) |
| • Red Silicone (USP Class VI) | • Teflon Encapsulated Silicone (USP Class VI) |
| • Black Viton (FDA) | • Teflon Encapsulated EPDM (USP Class VI) |
| • Black Viton (USP Class VI) | • Teflon Encapsulated Viton (USP Class VI) |
| • Black EPDM (FDA) | • Platinum Cured White Silicone (USP Class VI) |



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Features & Options

H-SERIES MANWAY FEATURES	H-SERIES MANWAY SIZES			
	8"-14"	16"-24"	26"-36"	38"-48"
STANDARD HANDLE ASSEMBLY	S	S	O	--
STANDARD HINGE ASSEMBLY	S	S	--	--
HEAVY DUTY HINGE ASSEMBLY	--	O	O	--
SUPER HINGE ASSEMBLY	--	O	O	--
STANDARD DUTY SPRING ASSIST	O	O	--	--
HEAVY DUTY SPRING ASSIST	--	O	O	--
LOCKING DEVICE (COVER ASSEMBLY)	O	O	O	--
O-RING GROOVE IN COLLAR RING	S	S	S	S
DOVETAIL GROOVE IN COLLAR RING	O	O	O	O
O-RING GROOVE IN COVER RING	O	O	O	O
DOVETAIL GROOVE IN COVER RING	O	O	O	O
STANDARD WINGNUTS	S	S	S	S
PRECISION BLUE KNOBS	O	O	O	O
MACHINED HEX NUTS	O	O	O	O

S = STANDARD | **O** = OPTIONAL | **--** = NOT AVAILABLE



* 18" (5) Lug H-Series is shown



* 16" (4) Lug H-Series is shown



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Pressure Chart

SIZE	LUGS	PRESSURE RATING (PSIG)				
		100°	200°	300°	350°	400°
8"	3	161	153	143	140	138
8"	4	215	201	191	187	184
10"	3	109	103	96	95	93
10"	4	146	137	129	127	124
12"	3	78	74	69	68	67
12"	4	105	99	93	91	89
12"	5	131	124	116	114	112
14"	3	59	56	52	51	50
14"	4	79	75	70	69	67
14"	5	99	93	87	86	84
14"	6	119	112	105	103	101
16"	4	62	58	54	54	53
16"	5	77	73	68	67	66
16"	6	93	88	82	81	79
16"	8	124	117	109	108	106
16"	10	140	140	137	135	131
18"	4	49	47	44	43	42
18"	5	62	58	55	54	53
18"	6	74	70	66	65	63
18"	8	99	94	88	86	85
18"	10	124	117	110	108	106
18"	12	131	124	124	121	117
20"	5	51	48	45	44	43
20"	6	61	58	54	53	52
20"	8	81	77	72	71	69
20"	10	102	96	90	89	87
20"	12	112	112	108	106	104

SIZE	LUGS	PRESSURE RATING (PSIG)				
		100°	200°	300°	350°	400°
22"	5	42	40	37	37	36
22"	6	51	48	45	44	43
22"	8	68	64	60	59	58
22"	10	85	80	75	74	73
22"	12	102	96	90	89	88
22"	14	112	106	102	99	96
24"	6	43	41	38	37	37
24"	8	57	54	51	50	49
24"	10	72	68	64	63	61
24"	12	86	82	76	75	74
24"	14	94	94	89	88	86
24"	16	94	94	94	91	88
26"	8	49	47	44	43	42
26"	10	62	58	55	54	53
26"	12	74	70	66	64	63
26"	14	87	82	77	75	74
26"	16	87	87	87	84	82
28"	8	43	40	38	37	36
28"	10	43	51	47	46	46
28"	12	64	61	57	56	55
28"	14	75	71	66	65	64
28"	16	81	81	76	75	73
30"	8	37	35	33	32	32
30"	10	47	44	41	41	40
30"	12	56	53	50	49	48
30"	14	66	62	58	57	56
30"	16	75	71	66	65	64

* H-Series Manways are available in sizes up to 48", inquire with your Sales Engineer for pressure ratings.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851



www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™





H-Series Manway Dimensional Charts

SIZE	"A" COLLAR O.D.	"B" OVERALL LENGTH	"C" OVERALL HEIGHT	"D" EYEBOLT B.C.	APPROX. WEIGHT
8"	8 5/8"	16 7/16"	12"	12 3/8"	45 LBS.
10"	10 3/4"	19"	12"	14 1/2"	52 LBS.



SIZE	"A" COLLAR O.D.	"B" OVERALL LENGTH	"C" OVERALL HEIGHT	"D" EYEBOLT B.C.	APPROX. WEIGHT
12"	12 1/2"	23"	12"	16 1/4"	48 LBS.
14"	14 1/2"	25"	12"	18 1/4"	56 LBS.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851



www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Dimensional Charts

SIZE	"A" COLLAR O.D.	"B" OVERALL LENGTH	"C" OVERALL HEIGHT	"D" EYEBOLT B.C.	APPROX. WEIGHT
16"	16 1/2"	24 1/2"	12"	20 1/4"	84 LBS.
18"	18 1/2"	26 1/2"	12"	22 1/4"	95 LBS.
20"	20 1/2"	28 1/2"	12"	24 1/4"	108 LBS.
22"	22 1/2"	30 1/2"	12"	26 1/4"	121 LBS.
24"	24 1/2"	32 1/2"	12"	28 1/4"	137 LBS.
26"	26 1/2"	34 1/2"	12"	30 1/4"	150 LBS.
28"	28 1/2"	36 1/2"	12"	32 1/4"	165 LBS.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851



www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Dimensional Charts

SIZE	"A" COLLAR O.D.	"B" OVERALL LENGTH	"C" OVERALL HEIGHT	"D" EYEBOLT B.C.	APPROX. WEIGHT
30"	30 1/2"	38 1/2"	13 1/16"	34 1/4"	184 LBS.
32"	32 1/2"	40 1/2"	13 5/16"	36 1/4"	201 LBS.
34"	34 1/2"	42 1/2"	14 3/16"	38 1/4"	222 LBS.
36"	36 1/2"	44 1/2"	14 5/8"	40 1/4"	240 LBS.
38"	38 1/2"	46 1/2"	14 3/4"	42 1/4"	260 LBS.
40"	40 1/2"	48 1/2"	15"	44 1/4"	278 LBS.
42"	42 1/2"	50 1/2"	15 1/4"	46 1/4"	300 LBS.
44"	44 1/2"	52 1/2"	15 9/16"	48 1/4"	320 LBS.
46"	46 1/2"	54 1/2"	15 11/16"	50 1/4"	342 LBS.
48"	48 1/2"	56 1/2"	16 1/16"	52 1/4"	363 LBS.



- * H-Series Manways weights are estimated based upon the manway size listed on the chart using the lowest lug configuration, hinge and handle.
- * For each additional lug added to the manway over the base lug number, add 5 lbs. to the weight.
- * If your application requires a spring assist, add 10 lbs. to the weight.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™

H-Series Manway Clamping Options



Standard Wingnuts

An H-Series Manway standard, and the most popular clamping option. This wingnut comes with a 180 Grit polished finish.



Precision Blue Knobs

A Biopharmaceutical favorite, this Blue Knob is typically used with situations require enclosed threads. This unit has a molded exterior with a Nitronic 60 insert.



Machined Hex Nuts

A unique Holloway America design, which is typically used with situations require enclosed threads and or when clearance issues arise due to the number of lugs on a manway. This option offers the lowest available profile.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Spring Assists

Holloway America offers (2) types of Spring Assists. Our Standard Duty & Heavy Duty. Each assist is designed to offer the operator an easy lifting experience over a wide range of sizes. Typically, lifting force is reduced well below to 50 lb.

Standard Duty Spring Assist



* Standard Duty Hinge is shown

- Sanitary, pharmaceutical design
- Designed for manways from 12" to 24"
- Enclosed Spring for easy operation and cleaning
- The assist comes installed and pre-set for optimal lifting.
- The assist will reduce the required lifting force to 50 lbs. or less
- Available "First Person" installation video
- Can be installed on any H-Series or K-Series Manway that has standard hinges

Heavy Duty Spring Assist



* Super Hinge is shown

- Sanitary, pharmaceutical design
- Designed for manways from 18" to 30"
- Enclosed Spring for easy operation and cleaning
- The assist comes installed and pre-set for optimal lifting.
- The assist will reduce the required lifting force to 50 lbs. or less



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851



www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404

The H-Series Manway™



H-Series Manway Required Lifting Force (In Lbs.)

SIZE	STANDARD HINGE	WITH STANDARD HINGE SPRING ASSIST	WITH SUPER HINGE AND HEAVY DUTY SPRING ASSIST
8"	11 LBS.	-58 LBS.	--
10"	14 LBS.	-38 LBS.	--
12"	17 LBS.	-25 LBS.	--
14"	20 LBS.	-16 LBS.	--
16"	25 LBS.	-8 LBS.	--
18"	29 LBS.	0 LBS.	-19 LBS.
20"	32 LBS.	5 LBS.	-10 LBS.
22"	37 LBS.	12 LBS.	-2 LBS.
24"	43 LBS.	20 LBS.	7 LBS.
26"	48 LBS.	26 LBS.	15 LBS.
28"	53 LBS.	33 LBS.	22 LBS.



- * H-Series Manways have a very light lifting force requirement. The spring assist is recommended on manways 18" and larger to further minimize the required lifting force.
- * The negative ratings above are stating that the force required to raise the cover is below 0 lbs. Indicating that the tension on the spring is already lifting the cover prior to any lifting force being applied. (See reference photo below).
- * The spring assist provides a cushioning effect upon closure, using the assemblies stored energy. This reduces the closure speed and the chance of operator smashing their fingers in the manway.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404