


Stock H-Series Manways™

The KING of Pharmaceutical Manways. The H-Series Manway is now IN STOCK and ready to ship. We currently stock the manway in 18" and 24" sizes.



Product Features

- Sanitary, pharmaceutical design
- Handles higher pressures with fewer lugs, providing easier access
- Standardized clamp / lug assemblies
- 1/4" Plate cover & collar
- 6" Standard collar length
- Provided with a standard hinge & handle
- Optional stainless enclosed spring assist is available
- O-Ring groove is provided in the collar ring
- Standard o-rings are 5/16" cross section



* 18" (5) Lug H-Series is shown with optional spring assist.

Materials & Finishes

- T-316L (Standard)
- All interior welds are ground "Smooth & Flush"
- All exterior welds can be ground "Smooth & Flush"
- Material finish is # 30 Ra ID / 30 Ra OD
- Standard o-ring is EPDM, White Silicone available at no additional charge. Other elastomers are available but could delay the shipment or ship after the manway.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_191015

Stock H-Series Manways™

H-Series Manway Stock Features

H-SERIES MANWAY NOTES	18"	24"
PART NUMBER	MWA24510164	MWA26810164
DESIGN PRESSURE	50 PSI	50 PSI
DESIGN TEMPERATURE	350° F	350° F
MATERIAL TYPE	316/316L	316/316L
# OF MANWAY LUGS	5	8
HINGE DESIGN	STANDARD DUTY	STANDARD DUT
LOCKING DEVICE (COVER ASSEMBLY)	AVAILABLE	AVAILABLE
SPRING ASSIST	AVAILABLE	AVAILABLE
KNOB STYLE	BLUE KNOB	BLUE KNOB



- * The manway pressure and temperature can be configured and slightly changed if needed. We show the manway rating at 350° F since it's the most common temperature request. Ratings to 400° F are available, but the pressure will be slightly less.
- * The manway is provided without a lock open device but this can be added for an additional charge.
- * The manway is provided without a spring assist but this can be added for an additional charge.
- * The standard manway knobs are the "Blue Knob" as shown above and on the previous page but can be swapped for the "Standard Wingnuts" or the "Machined Hex Nuts" if requested. The "Standard Wingnuts" would be a deduction; the "Machined Hex Nuts" would be an adder.
- * For a quotation on a stock manway, please call or email your components sales engineer today:
[Tina Williams at TWilliams@HollowayAmerica.com](mailto:Tina.Williams@HollowayAmerica.com)

H-Series Manway Clamping Options (Other than Blue Knob)



Standard Wingnuts



Machined Hex Nuts



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_191015

Stock H-Series Manways™



H-Series Manway Pressure Chart

SIZE	LUGS	PRESSURE RATING (PSIG)				
		100°	200°	300°	350°	400°
8"	3	161	153	143	140	138
8"	4	215	201	191	187	184
10"	3	109	103	96	95	93
10"	4	146	137	129	127	124
12"	3	78	74	69	68	67
12"	4	105	99	93	91	89
12"	5	131	124	116	114	112
14"	3	59	56	52	51	50
14"	4	79	75	70	69	67
14"	5	99	93	87	86	84
14"	6	119	112	105	103	101
16"	4	62	58	54	54	53
16"	5	77	73	68	67	66
16"	6	93	88	82	81	79
16"	8	124	117	109	108	106
16"	10	140	140	137	135	131
18"	4	49	47	44	43	42
18"	5	62	58	55	54	53
18"	6	74	70	66	65	63
18"	8	99	94	88	86	85
18"	10	124	117	110	108	106
18"	12	131	124	124	121	117
20"	5	51	48	45	44	43
20"	6	61	58	54	53	52
20"	8	81	77	72	71	69
20"	10	102	96	90	89	87
20"	12	112	112	108	106	104

SIZE	LUGS	PRESSURE RATING (PSIG)				
		100°	200°	300°	350°	400°
22"	5	42	40	37	37	36
22"	6	51	48	45	44	43
22"	8	68	64	60	59	58
22"	10	85	80	75	74	73
22"	12	102	96	90	89	88
22"	14	112	106	102	99	96
24"	6	43	41	38	37	37
24"	8	57	54	51	50	49
24"	10	72	68	64	63	61
24"	12	86	82	76	75	74
24"	14	94	94	89	88	86
24"	16	94	94	94	91	88
26"	8	49	47	44	43	42
26"	10	62	58	55	54	53
26"	12	74	70	66	64	63
26"	14	87	82	77	75	74
26"	16	87	87	87	84	82
28"	8	43	40	38	37	36
28"	10	43	51	47	46	46
28"	12	64	61	57	56	55
28"	14	75	71	66	65	64
28"	16	81	81	76	75	73
30"	8	37	35	33	32	32
30"	10	47	44	41	41	40
30"	12	56	53	50	49	48
30"	14	66	62	58	57	56
30"	16	75	71	66	65	64

* H-Series Manways are available in sizes up to 48", inquire with your Sales Engineer for pressure ratings.



Holloway America
720 N. Cedarbrook Ave.
Springfield, MO 65802

Phone: 417.863.0077
Toll Free: 866.659.0077
Fax: 417.863.8851

www.HollowayAmerica.com
info@HollowayAmerica.com
Datasheet: H-Series_150404